

BlastFelt



100% Polyester Acoustic Insulation Non-toxic, Non Asbestos, Non Chemical binder and ecological High performance sound absorption

BlastFelt Specifications




- 100% Recyclable
 - Highest Mold Resistance Rating
 - High Acoustical Performance Ratings
- Good heat and fire resistance elasticity and tensile strength.
- No manufacturing emissions, no waste pollution, environmental protection and can be recycled several times.

Product	BlastFelt
Material	100% Polyester fiber
Color	Mix gray
Size	600mm x 1200mm
Thickness	25 mm
Density	60 kg / m ³
Acoustic performance	Noise Reduction Coefficient (NRC) 0.95

Applications


STC 53 ✓



Layers

- 12mm Gypsum Board
- Steel structure
- 50mm BlastFelt
- 3mm BlastBlock
- 12mm Gypsum Board


STC 56 ✓



Layers

- 12mm Gypsum Board
- 3mm BlastBlock
- Steel structure
- 50mm BlastFelt
- 3mm BlastBlock
- 12mm Gypsum Board


STC 56 ✓



Layers

- 80mm Brick
- Steel structure
- 50mm BlastFelt
- 3mm BlastBlock
- 12mm Gypsum Board

STC 68 ✓



Layers

- X2 12mm Gypsum Boards
- 3mm BlastBlock
- Steel structure
- 50mm BlastFelt
- 50mm air space
- Steel structure
- 50mm BlastFelt
- 3mm BlastBlock
- X2 12mm Gypsum Boards

BlastBlock BV

Van der Takstraat 8
3071 LL Rotterdam, The Netherlands
+31 10 310 4928 Email: info@blast-block.com